

K018 / E

Delivery Bed (3 Motors)

Kenmak®

part of the Human Care Group



Technical Details	
Height Range (Without mattress)	62 – 85 cm
Trendelenburg Angle	12°
Reverse Trendelenburg Angle	12°
Backrest Angle	Min 0 – 68°
Length (Bumper to Bumper)	212 cm
Width (Bumper to Bumper)	104 cm
Lying Platform	195*71 cm
Safe Load Capacity	250 kg
Max Load Capacity	200 kg
Wheel Diameter	125 mm
Mattress Thickness	9 cm
Weight	130 kg

General Features

- Electrical height, and backrest adjustment
- Electrical Trendelenburg and reverse trendelenburg movement
- Electrical Fowler position
- Hand control panel
- 3 sections lying platform
- 2 pieces of side rails, made of easy-to-clean ABS Material
- Detachable ABS head and foot boards
- Retractable footrest
- 2 pieces of leg supports
- 2 pieces holding grips
- 1 piece stainless steel bowl
- Cross-Locking Castors
- Electrostatic Powder-Coated metal frame
- IV Pole
- Bumper protection against shocks
- Rechargeable backup battery

<http://www.kenmak.com.tr>

export@kenmak.com.tr

+90 232 274 17 17

LinkedIn

Instagram

Producing technology for your health.

